

Appl. No. 10/036,273
Amdt. dated September 28, 2004
Reply to final Office action of July 28, 2004

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1.-5. (Canceled).

6. (Previously presented) An electronic system, comprising:
- an electronics unit;
 - a temperature control logic coupled to said electronics unit; and
 - a fan coupled to said temperature control unit;
- wherein said temperature control unit implements a first temperature control protocol upon system initialization and changes to a second temperature control protocol if said electronics unit asserts a temperature signal, the first and second temperature control protocols effecting the speed of the fan;
- wherein said first temperature control protocol comprises at least two fan speeds, a higher fan speed being selected when the temperature, recorded by a temperature sensor, exceeds a first temperature threshold and a lower fan speed selected when the temperature is below the first temperature threshold; and
- wherein said second temperature control protocol comprises at least two fan speeds, a higher fan speed being selected when the temperature, recorded by a temperature sensor, exceeds a second temperature threshold and a lower fan speed selected when the temperature is below the second temperature threshold, said second temperature threshold being less than the first temperature threshold.

Appl. No. 10/036,273
Amdt. dated September 28, 2004
Reply to final Office action of July 28, 2004

7. (Currently amended) A computer system, comprising:
a CPU;
a fan controller coupled to said CPU; and
a fan coupled to said fan controller;
wherein said CPU is capable of implementing a plurality of temperature control protocols, all of said protocols effecting the speed of said fan as a function of only one variable temperature indication; and
wherein said CPU implements a first temperature control protocol upon system initialization and changes to a second temperature control protocol if said CPU asserts a temperature signal, wherein said first temperature control protocol causes the fan to spin at a different speed than the second temperature control protocol for the same level of the temperature indication;
wherein said first temperature control protocol comprises at least two fan speeds, a higher fan speed being selected when the temperature, recorded by a temperature sensor, exceeds a first temperature threshold and a lower fan speed selected when the temperature is below the first temperature threshold; and
wherein said second temperature control protocol comprises at least two fan speeds, a higher fan speed being selected when the temperature, recorded by a temperature sensor, exceeds a second temperature threshold and a lower fan speed selected when the temperature is below the second temperature threshold, said second temperature threshold being less than the first temperature threshold.
8. (Original) The system of claim 7 wherein said CPU implements a third temperature control protocol that is louder than said second temperature control protocol.

Appl. No. 10/036,273
Amdt. dated September 28, 2004
Reply to final Office action of July 28, 2004

9. (Original) The system of claim 8 wherein said second temperature control protocol is implemented the first time the temperature signal is asserted and the third temperature control protocol is implemented the second time the temperature signal is asserted.

10.-12. (Canceled).

13. (Original) The system of claim 7 wherein said CPU internally monitors its temperature and asserts the temperature signal which indicates the CPU's internal temperature has reached a threshold.

14. (Currently amended) A method of controlling temperature in an electronic system, comprising:

initializing the system to a first temperature control protocol that reacts to only one temperature indication;

determining that a temperature associated with the electronic system has reached a threshold; and

switching from the first temperature control protocol to a second temperature control protocol that also reacts to only one temperature indication and the same temperature indication as for the first temperature control protocol, said first temperature control protocol being quieter on average than said second temperature control protocol and wherein said first temperature control protocol causes a fan to spin at a different speed than the second temperature control protocol for the same level of the temperature indication;

wherein said first temperature control protocol comprises at least two fan speeds, a higher fan speed being selected when the temperature recorded by a temperature sensor exceeds a first temperature threshold and a lower fan speed selected when the temperature is below the first temperature threshold;

Appl. No. 10/036,273
Amdt. dated September 28, 2004
Reply to final Office action of July 28, 2004

wherein said second temperature control protocol comprises at least two fan speeds, a higher fan speed being selected when the temperature recorded by a temperature sensor exceeds a second temperature threshold and a lower fan speed selected when the temperature is below the second temperature threshold, said second temperature threshold being less than the first temperature threshold.

15. (Original) The method of claim 14 further including switching to a third temperature control protocol that is louder than said second temperature control protocol.

16. (Original) The method of claim 15 wherein switching to the third temperature control protocol occurs if it is determined that the threshold has again been reached.

17.-19. (Canceled).

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.